



4MP POE IP Bullet camera



- 1:4MP high definition image quality, Clearer picture quality,
- 2:H.265/H.264 Video Compression
- 3:8PCS SMD IR LED,25m IR Distance
- 4:2.8-12mm Varifocus Lens
- 5:IP66 Waterproof Metal Housing
- 6:Support ONVIF ,P2P Cloud service
- 7:Support POE

Model NO	SS-319BIP4MF
Camera type	Bullet IP camera
Frames Rates	PAL:25fps. NTSC:30fps
Image Sensor	1/2.8"CMOS with ICR
Resolution	4MP
DSP	Dual Core 32-bit DSP
Min. Illumination	Color 0.01Lux@F1.2
	B/W 0.001 Lux@F1.2
Adjust Parameter	DWDR,BLC,DNR,AE,AGC,D&N,Mirror,Flip,etc.
s	
Compression	H.265 Main profile
Stream	support dual stream,AVI format
Bit Rate	support 0.1M ~8Mbps bit rate adjustable
Input and output	1ch input(microphone),1ch output(Speaker&micphone) Optional
Compression	G.711 compression,support two-way audio intercom,support audio and video synchronized output
Alarm Types	Motion Detection, Video Blind , Video Loss
WEB Browser	Support WEB remote config(IE, Safari, Google Chrome, Firefox etc.)
Smart Phone	Mobile remote Monitoring (iPhone,Android,Windows Mobile,BlackBerry,Symbian)
CMS Software	VMS Software(multiple devices management system)
Network	1*RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP
ONVIF	Support (ONVIF 2.0)
POE	Support
WIFI	N/A
Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish
	Portuguese, Russian, Spanish, Thai, S-Chinese, T-Chinese and Turkish
Lens Mount	2.8-12mm Varifocus lens
Infrared Luminary	8pcs IR LED SMD leds
Infrared Wave	850 nm



length	
IR Range	25m
Waterproof	IP 66
I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)
Supplied Voltage	DC12V/PoE(802.3af/820.3at)
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA
Box Size	270mm x 135mm x 130mm